### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

### (19) World Intellectual Property Organization

International Bureau



# 

(43) International Publication Date 3 February 2005 (03.02.2005)

**PCT** 

# (10) International Publication Number WO 2005/011351 A1

(51) International Patent Classification7:

H05K 13/04

(21) International Application Number:

PCT/IB2004/051270

(22) International Filing Date:

21 July 2004 (21.07.2004)

(25) Filing Language:

English

(26) Publication Language:

**English** 

(30) Priority Data:

03102344.3


30 July 2003 (30.07.2003) EP

- (71) Applicant (for all designated States except US): ASSEM-BLEON N.V. [NL/NL]; De Run 1110, NL-5503 LA Veldhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): VAN DE VEN, Johannes, T., A. [NL/NL]; c/o De Run 1110, NL-5503 LA Veldhoven (NL).

- (74) Agent: DEGUELLE, Wilhelmus, H., G.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: COMPONENT PLACEMENT DEVICE, NOZZLE EXCHANGE DEVICE AS WELL AS METHOD FOR THE EXCHANGE OF NOZZLES



(57) Abstract: Component placement device (1) which is provided with a holder (2) as well as a nozzle (3) provided with a duct (10), which nozzle (3) is connected to the holder (2). The nozzle (3) is detachably connected to the holder (2). The holder (2) is furthermore provided with a passage (5) which is connected to the duct (10). The nozzle (3) which is detachably connected to the holder (2) is exchangeable by means of a nozzle exchange device.

## WO 2005/011351 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### **Declaration under Rule 4.17:**

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA,

SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.